



HI-VALLEY CHEMICAL

LABORATORY PRODUCTS

1134 W. 850 N. CENTERVILLE, UT 84014
(801) 295-9591 Fax (801) 295-9448
www.hvchemical.com

Hexane

1

PRODUCT AND COMPANY IDENTIFICATION

Product Identifier: Hexane
SDS Number: R-098
Product Code: 514270-PT, 514270-QT, 514270-1, 514270-5, 514270-55
Revision Date: 6/4/2018
Version: 1

Supplier Details: High Valley Products, Inc.
1134 West 850 North
Centerville, Utah 84014

Phone: 801-295-9591
Email: sales@hvchemical.com
Internet: www.hvchemical.com
Emergency: PERS: 800-633-8253

2

HAZARDS IDENTIFICATION

Classification of Substance

GHS Classification in Accordance with 29 CFR 1910 (OSHA HCS):

Physical, Flammable Liquids, 2
Health, Aspiration hazard, 1
Health, Skin corrosion/irritation, 2
Health, Specific target organ toxicity - Single exposure, 3
Health, Reproductive toxicity, 2
Health, Specific target organ toxicity - Repeated exposure, 2
Environmental, Hazards to the aquatic environment - Acute, 2
Environmental, Hazards to the aquatic environment - Chronic, 2

GHS Label Elements, Including Precautionary Statements

GHS Signal Word: **DANGER**

GHS Hazard Pictograms:



GHS Hazard Statements:

H225 - Highly flammable liquid and vapor
H304 - May be fatal if swallowed and enters airways
H315 - Causes skin irritation
H336 - May cause drowsiness or dizziness
H361 - Suspected of damaging fertility or the unborn child
H373 - May cause damage to organs through prolonged or repeated exposure
H401 - Toxic to aquatic life
H411 - Toxic to aquatic life with long lasting effects

GHS Precautionary Statements:

P201 - Obtain special instructions before use.
P202 - Do not handle until all safety precautions have been read and understood.
P210 - Keep away from heat/sparks/open flames/hot surfaces. No smoking
P233 - Keep container tightly closed.
P240 - Ground/bond container and receiving equipment.
P241 - Use explosion-proof electrical/ventilating/light/equipment.

P242 - Use only non-sparking tools.
 P243 - Take precautionary measures against static discharge.
 P260 - Do not breathe dust/fume/gas/mist/vapors/spray.
 P264 - Wash skin thoroughly after handling.
 P271 - Use only outdoors or in a well-ventilated area.
 P273 - Avoid release to the environment.
 P280 - Wear protective gloves/protective clothing/eye protection/face protection.
 P301+310 - IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician.
 P303+361+353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.
 P304+340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.
 P308+313 - IF exposed or concerned: Get medical advice/attention.
 P321 - Specific treatment (see _ on this label).
 P331 - Do NOT induce vomiting.
 P332+313 - If skin irritation occurs: Get medical advice/attention.
 P362 - Take off contaminated clothing and wash before reuse.
 P370+378 - In case of fire: Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.for extinction.
 P391 - Collect spillage.
 P403+233 - Store in a well ventilated place. Keep container tightly closed.
 P403+235 - Store in a well ventilated place. Keep cool.
 P405 - Store locked up.
 P501 - Dispose of contents/container to local regulations.

3 COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Ingredients		
CAS#	%	Chemical Name
110-54-3	100%	Hexane

4 FIRST AID MEASURES

Inhalation: If inhaled, move person to fresh air. If not breathing, give artificial respiration. Consult a physician.
Skin Contact: Wash with soap and water. Consult a physician.
Eye Contact: Immediately flush eyes with large amounts of water for at least 15 minutes, lifting eyelids occasionally to facilitate irrigation.
Ingestion: Do not induce vomiting unless instructed to do so by a physician. Never give anything by mouth to an unconscious person. Rinse mouth with water. Consult a physician.

5 FIRE FIGHTING MEASURES

Extinguishing media
 Suitable extinguishing media
 Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Special hazards arising from the substance or mixture
 No data available

Advice for firefighters
 Wear self-contained breathing apparatus for firefighting if necessary.

Further information
 No data

6 ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures:

Wear respiratory protection. Avoid breathing vapors, mist or gas. Ensure adequate ventilation. Evacuate personnel to safe areas.

Environmental precautions:

Do not let product enter drains.

Methods and materials for containment and cleaning up:

Soak up with inert absorbent material and dispose of as hazardous waste. Keep in suitable, closed containers for disposal.

7 HANDLING AND STORAGE

Handling Precautions: Avoid contact with eyes, skin, or clothing.
Avoid breathing vapors or mist.

Storage Requirements: Keep container tightly closed.
Store in cool/dry area.

8 EXPOSURE CONTROLS/PERSONAL PROTECTION

Personal Protective Equipment:

Hexane (110-54-3) [100%]

Personal protective equipment

Eye/face protection: Face shield and safety glasses Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU).

Skin protection: Handle with gloves. Gloves must be inspected prior to use. Use proper glove removal technique (without touching gloves outer surface) to avoid skin contact with this product. Dispose of contaminated gloves after use in accordance with applicable laws and good laboratory practices. Wash and dry hands.

Full contact: Material: Nitrile rubber Minimum layer thickness: 0.4 mm Break through time: 480 min
Material tested:Camatril (KCL 730 / Aldrich Z677442, Size M)

Splash contact: Material: Nitrile rubber Minimum layer thickness: 0.2 mm Break through time: 30 min
Material tested:Dermatril P (KCL 743 / Aldrich Z677388, Size M) data source: KCL GmbH, D-36124 Eichenzell, phone +49 (0)6659 87300, e-mail sales@kcl.de, test method: EN374 If used in solution, or mixed with other substances, and under conditions which differ from EN 374, contact the supplier of the CE approved gloves. This recommendation is advisory only and must be evaluated by an industrial hygienist and safety officer familiar with the specific situation of anticipated use by our customers. It should not be construed as offering an approval for any specific use scenario.

Body Protection: Complete suit protecting against chemicals, Flame retardant antistatic protective clothing, The type of protective equipment must be selected according to the concentration and amount of the dangerous substance at the specific workplace.

Respiratory protection: Where risk assessment shows air-purifying respirators are appropriate use a full-face respirator with multi- purpose combination (US) or type AXBEK (EN 14387) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Control of environmental exposure: Prevent further leakage or spillage if safe to do so. Do not let product enter drains. Discharge into the environment must be avoided.

Exposure Guideline

Hexane (110-54-3) [100%]

Components with workplace control parameters

TWA 50 ppm USA. ACGIH Threshold Limit Values
(TLV)

Central Nervous System impairment

Eye irritation

Peripheral neuropathy

Substances for which there is a Biological Exposure Index or Indices
(see BEI section)

Danger of cutaneous absorption

TWA 50 ppm USA. NIOSH Recommended
180 mg/m³ Exposure Limits

TWA 500 ppm USA. Occupational Exposure Limits
1,800 mg/m³ (OSHA) - Table Z-1 Limits for Air
Contaminants

The value in mg/m³ is approximate.

TWA 50 ppm USA. OSHA - TABLE Z-1 Limits for
180 mg/m³ Air Contaminants - 1910.1000

9 PHYSICAL AND CHEMICAL PROPERTIES

Appearance:	Colorless.
Physical State:	Liquid
Solubility:	Insoluble
Specific Gravity or Density:	0.659
Boiling Point:	69 °C (156 °F)
Freezing or Melting Point:	-95 °C (-139 °F)
Flash Point:	-26.0 °C (-14.8 °F) - closed cup
Partition Coefficient:	log Pow: 3.90 - 4.11
Vapor Pressure:	341.3 hPa (256.0 mmHg) at 37.7 °C (99.9 °F) 176.0 hPa (132.0 mmHg) at 20.0 °C (68.0 °F)
Potentia Hydrogenii:	7.0
Evaporation Rate:	15.8
Upper Flammability Limit and Lower Flammability Limit:	7.7 %(V) / 1.2 %(V)

10 STABILITY AND REACTIVITY

Reactivity:	No data available
Chemical Stability:	Stable under recommended storage conditions.
Conditions to Avoid Identification:	Avoid moisture. Heat, flames and sparks.
Materials to Avoid Identification:	Oxidizers

11 TOXICOLOGICAL INFORMATION

Hexane (110-54-3) [100%]

Information on toxicological effects

Acute toxicity:

LD50 Oral - rat - 25,000 mg/kg

LC50 Inhalation - rat - 4 h - 48000 ppm

Dermal: no data available

Skin corrosion/irritation: no data available

Serious eye damage/eye irritation: Eyes - rabbit Result: Mild eye irritation

Respiratory or skin sensitisation: no data available

Germ cell mutagenicity: no data available

Carcinogenicity:

Carcinogenicity - rat - Inhalation:

Tumorigenic: Carcinogenic by RTECS criteria. Tumorigenic Effects: Testicular tumors.

IARC: No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

ACGIH: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by ACGIH.

NTP: No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

OSHA: No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

Reproductive toxicity: no data available

Overexposure may cause reproductive disorder(s) based on tests with laboratory animals. Suspected human reproductive toxicant
Suspected of damaging fertility.

Specific target organ toxicity - single exposure: May cause drowsiness or dizziness.

Specific target organ toxicity - repeated exposure: Ingestion - May cause damage to organs through prolonged or repeated exposure. -
Nervous system

Aspiration hazard: May be fatal if swallowed and enters airways.

Additional Information:

RTECS: MN9275000

Prolonged or repeated contact with skin may cause: defatting, Dermatitis, Contact with eyes can cause: Redness, Blurred vision, Provokes tears., Effects due to ingestion may include: Gastrointestinal discomfort, Central nervous system depression, Lung irritation, chest pain, pulmonary edema, giddiness, slowed reaction time, slurred speech, Headache, Dizziness, Drowsiness, Unconsciousness
Testes. - Irregularities - Based on Human Evidence

12

ECOLOGICAL INFORMATION

Hexane (110-54-3) [100%]

Information on ecological effects

Toxicity:

Toxicity to fish LC50 - Pimephales promelas (fathead minnow) - 2.5 mg/l - 96.0 h.

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 3,878.00 mg/l - 48 h.
other aquatic invertebrates

Toxicity to algae EC50 - Chlorella vulgaris (Fresh water algae) - 12,840.00 mg/l - 3 h.

EC50 - SKELETOMA - 0.30 mg/l - 8 h

Persistence and degradability: no data available

Bioaccumulative potential: no data available

Mobility in soil: no data available

Results of PBT and vPvB assessment PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal.
Toxic to aquatic life.

13

DISPOSAL CONSIDERATIONS

Dispose of in accordance with local regulations.

14

TRANSPORT INFORMATION

UN1208, Hexanes, 3, PGII

Component (CAS#) [%] - CODES

RQ(5000LBS), Hexane (110-54-3) [100%] CERCLA, HAP, MASS, OSHAWAC, PA, SARA313, TSCA, TXAIR

**WARNING**



This product can expose you to chemicals including , which @VERB@ known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.

Regulatory CODE Descriptions

RQ = Reportable Quantity
 CERCLA = Superfund clean up substance
 HAP = Hazardous Air Pollutants
 MASS = MA Massachusetts Hazardous Substances List
 OSHAWAC = OSHA Workplace Air Contaminants
 PA = PA Right-To-Know List of Hazardous Substances
 SARA313 = SARA 313 Title III Toxic Chemicals
 TSCA = Toxic Substances Control Act
 TXAIR = TX Air Contaminants with Health Effects Screening Level

NFPA: Health = 2, Fire = 3, Reactivity = 0, Specific Hazard = n/a

HMIS III: Health = 2, Fire = 3, Physical Hazard = 0

**Disclaimer:**

Although reasonable care has been taken in the preparation of this document, we extend no warranties and make no representations as to the accuracy or completeness of the information contained herein, and assume no responsibility regarding the suitability of this information for the user's intended purposes or for the consequences of its use. Each individual should make a determination as to the suitability of the information for their particular purpose(s).

Revision Date: 6/4/2018